

石頭金

MetalMiracle[®]

Slewing Bearing with outer flange and internal gear including but not limited to:

			216	340	39	324	252	20	20	M6	M6	310	238	30	5	34	34	279	277	4	56	224	300	10
VLI200414N ZT			325	518	56	490	375	8	12	φ18	M12	458.5	350	40	11.5	44.5	47.5	415.5	412.5	5	67	335	600	28.5
VLI 20 0414N ZT RL2			325	516	56	490	375	8	12	φ18	M12	456	350	40	11.5	44.5	47.5	415.5	412.5	5	67	335	300	36.3
VLI200414N			325	518	56	490	375	8	12	18	M12		350	40	8.5	44.5	47.5	415.5	412.5	5	67	335	295	27.5
	232.20.0400.013		326.5	518	56	490	375	8	12	18	M12			45.5	10.5	45.5	45.5	415.5	412.5	5	67	335	250	27.1
	232.20.0400.503		326.5	518	56	490	375	16	12	18	M12			45.5	10.5	45.5	45.5	415.5	412.5	5	67	335	250	26.9
	232.21.0475.013		326.5	517	56	490	375	8	12	18	M12			45.5	10.5	45.5	45.5	415.5	411	5	67	335	250	27.1
		1.505.20.00.C	326.5	518	56	490	375	8	12	φ18	M12	453		46	10	46	46	415.5	412.5	5	67	335	500	35.4
VLI200544N ZT			444	648	56	620	505	10	16	φ18	M12	588.5		44.5	11.5	44.5	47.5	545.5	542.5	6	76	456	790	40.6
VLI200544N			444	648	56	620	505	10	16	18	M12			44.5	11.5	44.5	47.5	545.5	542.5	6	76	456	385	38
	232.20.0500.013		445.2	648	56	620	505	10	16	18	M12			45.5	10.5	45.5	45.5	545.5	542.5	6	76	456	330	36.9
	232.20.0500.503		445.2	648	56	620	505	20	16	18	M12			45.5	10.5	45.5	45.5	545.5	542.5	6	76	456	330	36.7
	232.21.0575.013		445.2	647	56	620	505	10	16	18	M12			45.5	10.5	45.5	45.5	545.5	541	6	76	456	330	36.9
		1.650.20.00.C	445.2	648	56	620	505	10	16	φ18	M12	583		46	10	46	46	545.5	542.5	6	76	456	700	40.2
VLI200644N ZT			546	748	56	720	605	12	18	φ18	M12	688.5		44.5	11.5	44.5	47.5	645.5	642.5	6	93	558	900	47.4
VLI200644N			546	748	56	720	605	12	18	18	M12			44.5	8.5	44.5	47.5	645.5	642.5	6	93	558	455	45
	232.20.0600.013		547.2	748	56	720	605	12	18	18	M12			45.5	10.5	45.5	45.5	645.5	642.5	6	93	558	390	43.7
	232.20.0600.503		547.2	748	56	720	605	24	18	18	M12			45.5	10.5	45.5	45.5	645.5	642.5	6	93	558	390	43.4
	232.21.0675.013		547.2	747	56	720	605	12	18	18	M12			45.5	10.5	45.5	45.5	645.5	641	6	93	558	390	43.7
		1.750.20.00.C	547.2	748	56	720	605	12	18	φ18	M12	683		46	10	46	46	645.5	642.5	6	93	558	780	53.3
VLI200744N ZT			648	848	56	820	705	12	20	φ18	M12	788.5		44.5	11.5	44.5	47.5	745.5	742.5	6	110	660	530	54
VLI200744N			648	848	56	820	705	12	20	18	M12			44.5	8.5	44.5	47.5	745.5	742.5	6	110	660	530	51.5
	232.20.0700.013		649.2	848	56	820	705	12	20	18	M12			45.5	10.5	45.5	45.5	745.5	742.5	6	110	660	450	51.1
	232.20.0700.503		649.2	848	56	820	705	24	20	18	M12			45.5	10.5	45.5	45.5	745.5	742.5	6	110	660	450	50.8
	232.21.0775.013		649.2	847	56	820	705	12	20	18	M12			45.5	10.5	45.5	45.5	745.5	741	6	110	660	450	51.1
		1.850.20.00.C	649.2	848	56	820	705	12	20	φ18	M12	783		46	10	46	46	745.5	742.5	6	110	660	910	63.1
VLI200844N ZT			736	948	56	920	805	14	20	φ18	M12	888.5		44.5	11.5	44.5	47.5	845.5	842.5	8	94	752	1200	65.2

VLI200844N			736	948	56	920	805	14	20	18	M12			44.5	8.5	44.5	47.5	845.5	842.5	8	94	752	600	61.5
	232.20.0800.013		737.6	948	56	920	805	14	20	18	M12			45.5	10.5	45.5	45.5	845.5	842.5	8	94	752	510	61.6
	232.20.0800.503		737.6	948	56	920	805	28	20	18	M12			45.5	10.5	45.5	45.5	845.5	842.5	8	94	752	510	61.3

Contact Us:

Sichuan MetalMiracle Industry Corp.

Tianfu Avenue South Section NO.2039, HuaYang, Chengdu Tianfu New Area, China.

Industry area, ChongZhou, Chengdu, China.

Industry area, ChongQing, China.

Mechanical Industry area, Taibai, Maanshan, China.

Tel. 86 28 85718737 Email: simon@lycores.com www.lycores.com